

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
25 August 2005 (25.08.2005)

PCT

(10) International Publication Number
WO 2005/078835 A2

- (51) International Patent Classification⁷: **H01M 8/00** (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (21) International Application Number:
PCT/JP2005/002197
- (22) International Filing Date: 8 February 2005 (08.02.2005)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2004-037148 13 February 2004 (13.02.2004) JP
- (71) Applicant (for all designated States except US): NISSAN MOTOR CO., LTD. [JP/JP]; 2, Takara-cho, Kanagawa-ku, Yokohama-shi, Kanagawa 2210023 (JP).
- (72) Inventor; and
(75) Inventor/Applicant (for US only): KAGAMI, Fumio.
- (74) Agents: MIYOSHI, Hidekazu et al.: Toranomon Kotohira Tower, 2-8, Toranomon 1-chome, Minato-ku, Tokyo 1050001 (JP).
- Published:
— without international search report and to be republished upon receipt of that report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FUEL CELL SYSTEM AND RELATED METHOD



(57) Abstract: A fuel cell system (S1, S2, S3, S4, S5) includes a fuel cell (1) supplied with fuel and oxidizer to generate electric power, a heating mechanism (6, 31, 32) executing a heating to the fuel cell, a temperature detector (7) detecting a temperature of the fuel cell, and a controller (5) operative to calculate a temperature drop speed of the fuel cell, during a period in which the temperature of the fuel cell is lowering, using the temperature of the fuel cell detected by the temperature detector to control the heating mechanism such that the temperature drop speed is kept equal to or less than a given speed.